



# QUICK TOUCH

Anchor's Quick Touch formulations are heavy-duty enamels specifically designed for applications requiring fast dry times. Quick Touch enamels are especially suitable for:

## Original Equipment Manufacturing

- Heavy Duty Machinery & Equipment
- Farm and Agriculture Machinery & Equipment
- Steel Storage & Waste Containers
- Oil & Gas Equipment

## Industrial Maintenance

- Heavy Duty Machinery & Equipment
- Farm and Agriculture Machinery & Equipment
- Steel Storage & Waste Containers
- Oil and Gas Equipment

## FEATURES & BENEFITS

- **Proven Performance:** Our Quick Touch 1200 series has been providing fast-dry protection since 1962.
- **Fast Dry Times:** Ambient dry times as fast as 15 minutes to touch and 40 minutes to recoat.
- **Easy to Use:** Quick Touch enamels are available in convenient, ready-to-spray versions.
- **VOC and HAPS Compliant:** The LoVOC and LoHAPS series represent our commitment to providing environmentally compliant products that meet the performance expectations of the original 1200 series.

## CUSTOMERS USING **QUICK TOUCH** HAVE INCLUDED:

- One of the world's leading providers of manufacturing, sales and equipment support for automatic welding and pipeline equipment, field joint coating and inspection services.
- One of the world's leading providers of construction equipment in the pipeline industry.
- A leading North American manufacturer of waste handling and recycling equipment.

# QUICK TOUCH ENAMELS

Anchor's Quick Touch formulations are heavy-duty enamels specifically designed for applications requiring fast dry times. We also have options to meet all federal environmental requirements.

## Particularly suited for:

- Original Equipment Manufacturing
- Industrial Maintenance
- Heavy Duty Machinery & Equipment
- Farm and Agriculture
- Machinery & Equipment
- Steel Storage & Waste Containers
- Oil & Gas Equipment



## Features & Benefits:

- Fast dry times
- High Gloss
- High Durability
- Easy to Use
- Excellent Color Retention
- VOC and HAPS compliant options
- Heat Resistant up to 150° F (continuous) and spikes up to 250° F.

<b>Dry Time:</b>	15 min to touch, 40 minutes to recoat*
<b>Colors</b>	A variety of colors available
<b>Gloss:</b>	High Gloss
<b>Coverage Rate</b>	389 ft <sup>2</sup> @ suggested thickness
<b>Volume Solids</b>	33.93%**

\*At 75° F \*\*Varies by color