

SAF-T-GARD II

Anchor's Saf-T-Gard II heavy-duty enamels are specifically designed for industrial maintenance applications. These enamels are incredibly easy to apply and provide durable protection suitable for:

INDUSTRIAL MAINTENANCE

- General Industrial Applications
- Heavy Duty Equipment
- Farm and Agriculture Equipment
- Oil and Gas Equipment

FEATURES & BENEFITS

- **Proven Performance:** Our original Saf-T-Gard formula has been protecting industrial assets from since 1962. **Saf-T-Gard II** is a modified and enhanced formulation that provides the most optimal performance available today.
- **Simple Application:** Can be applied by brush, roll, spray, or mitt - whatever method you prefer.
- **Gloss Retention:** ASTM D4587 - 84% retention of 60-degree gloss after 312 hours.*
- **Polyurethane Hardener:** An available polyurethane hardener is easy to add and improves the performance of Saf-T-Gard. II
- **Superior Adhesion:** Saf-T-Gard II enamels stick to just about everything.

*Test results from 900 plus J1100 system.

CUSTOMERS USING **SAF-T-GARD** HAVE INCLUDED:

- One of the largest refiners, transporters and marketers of transportation fuels, lubricants, petrochemicals and industrial products in the world
- One of the largest offshore drilling companies in the U.S.
- The second largest producer of natural gas in the U.S.

SAF-T-GARD II ENAMELS

Anchor's Saf-T-Gard II heavy-duty enamels are specifically designed for industrial maintenance applications. These enamels are incredibly easy to apply and provide a durable protection suitable for a wide variety of applications.

Particularly suited for:

- General Industrial Applications
- Heavy Duty Equipment
- Farm and Agriculture Equipment
- Oil and Gas Equipment
- Industrial Maintenance
- Offshore Drilling

Features & Benefits:

- Excellent abrasion/ chemical/ weather resistance
- High Gloss
- VOC Compliant
- Heat Resistance: can withstand continuous heat up to 150° F and spikes of up to 250° F.
- Easy to apply
- Superior adhesion



Dry Time:	3.5 hours to touch, 8 hours to recoat*
Colors	A variety of colors available
Gloss:	High Gloss
Coverage Rate	483 ft ² @ suggested thickness
Volume Solids	54.90%**

*At 75° F **Varies by color